

# blueplanet 110 + 125 TL3-US

String inverters for commercial and industrial PV systems.



## The trendsetters among inverters.

Cost-saving due to 480 V line voltage and integrated section switches

Optimised for PV modules with 1000 V and 1500 V

Highest efficiency and overload capacity through silicon carbide technology

High power density for easy handling and logistics

Lean commissioning and updates via remote services

Decentralised design or 'Virtual Central' concept possible

## Technical Data

DC input data	110 TL3-US	125 TL3-US
Max. recommended PV generator power	165 000 W	187 500 W
MPP range	705 – 1 300 V	705 – 1 300 V
Operating range	705 – 1 450 V	705 – 1 450 V
Rated DC voltage / start voltage	730 V / 805 V	730 V / 805 V
Max. no-load voltage	1 500 V	1 500 V
Max. input current	160 A	183 A
Max. short circuit current $I_{sc,max}$	300 A	300 A
Number of MPP tracker	1	1
Connection per tracker	1 - 2	1 - 2
AC output data		
Rated output	110 000 VA	125 000 VA
Max. power	110 000 VA	125 000 VA
Line voltage	480 V (3P+PE)	480 V (3P+PE)
Voltage range (Ph-Ph)	300 – 580 V	300 – 552 V
Rated frequency (range)	50 Hz / 60 Hz (45 – 65 Hz)	50 Hz / 60 Hz (45 – 65 Hz)
Rated current	3 x 132.3 A	3 x 150.5 A
Max. current	3 x 132.3 A	3 x 152.0 A
Reactive power / cos phi		0 – 100 % Snom / 0,30 ind. – 0,30 cap.
Max. total harmonic distortion (THD)	≤ 3 %	≤ 3 %
Number of grid phases	3	3
General data		
Max. efficiency	99.1 %	99.0 %
Europ. efficiency	98.8 %	98.7 %
CEC efficiency	98.8 %	98.7 %
Standby consumption	5 W	6 W
Circuitry topology	transformerless	transformerless
Mechanical data		
Display	LEDs	LEDs
Control units	webserver, supports mobile devices	webserver, supports mobile devices
Interfaces	Ethernet (Modbus TCP, Sunspec), RS485 (KACO-protocol), USB, optional: 4-DI, WIFI	
Fault signalling relay	potential-free NOC max. 30 V / 1 A	potential-free NOC max. 30 V / 1 A
DC connection	cable lug, max. 240 mm <sup>2</sup> (0.372 in <sup>2</sup> ) Cu or Al	
AC connection	cable lug, max. 240 mm <sup>2</sup> (0.372 in <sup>2</sup> ) Cu or Al	
Ambient temperature	-25 °C – +60 °C <sup>1)</sup>	-25 °C – +60 °C <sup>1)</sup>
Humidity	0 – 100 %	0 – 100 %
Max. installation elevation (above MSL)	3 000 m	3 000 m
Min. distance from coast	500 m	500 m
Cooling	temperature controlled fan	temperature controlled fan
Protection class	IP66 / NEMA 4X	IP66 / NEMA 4X
Noise emission	59.2 db (A)	59.2 db (A)
H x W x D	719 x 699 x 460 mm	719 x 699 x 460 mm
Weight	78.2 kg	78.2 kg
Certifications	IEC 62109-1/-2, EN 61000-6-1/-2/-4, EN 61000-3-11/-12, EN 55011 group 1, class A	
Safety	EN 62920 Emission class A/Immunity class A UL62109-1, UL1741, CSA-C22.2 No.107.1, CSA-C22.2 No.62109-1,CSA-C22.2 No.62109-2	
Grid connection rule	overview see homepage / download area	

<sup>1)</sup> Power derating at high ambient temperatures

Versions	S	XL
Number of DC inputs	1 - 2	1 - 2
DC switch	-	✓
DC SPD	Type 1 + 2	Type 1 + 2
AC SPD	○	○
RS485 interface SPD	○	○
Ethernet interface SPD	○	○
PID Set	○	○

standard = ✓ upgradeable = ○

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. This current version replaces all older versions. Download the most current version at: [www.kaco-newenergy.com](http://www.kaco-newenergy.com)